

SEPARATOR FOR ALKALINE BATTERY AND ALKALINE BATTERY

Publication number: JP8273653

Publication date: 1996-10-18

Inventor: NISHIKITANI YOSHINORI; AKITA SEIICHI; IKEDA HIROYUKI; KURODA NOBUYUKI

Applicant: NIPPON OIL CO LTD

Classification:

- international: C08K3/38; C08L29/04; H01M2/16; H01M6/04; H01M10/24; C08K3/00; C08L29/00; H01M2/16; H01M6/04; H01M10/24; (IPC1-7): H01M2/16; C08K3/38; C08L29/04; H01M6/04; H01M10/24

- european:

Application number: JP19950075152 19950331

Priority number(s): JP19950075152 19950331

Report a data error here

Abstract of JP8273653

PURPOSE: To enhance stability, and particularly lengthen the cycle service life of a secondary battery by forming an alkaline battery having a separator. **CONSTITUTION:** A separator for an alkaline battery which is substantially formed of a cross linked body obtained by cross-linking polyvinyl alcohol under the existence of a cross-linking agent and on which the cross-linking agent 13 sodium tetraboric acid and/or its hydrate and whose cross-linked body is formed independently or integrally with a mesh-like structure body and is characterized by having a sheet-like shape or the like and an alkaline battery having these, are provided. A separator is excellent in electrolyte resistance, dendrite resistance and an electrolyte keeping characteristic, and is useful since ion conductivity is excellent.

Data supplied from the *esp@cenet* database - Worldwide